

Single and Dual Function Hot Plates

**For preheat,
rework and
reflow!**

**Lead Free*
High Temp
Compatible!!**



GF-DL-HT Dual Hot Plate

Used for a variety of heating applications which include preheat, rework, reflow and curing of printed circuit board assemblies.



GF-SL-HT Single Hot Plate

GF-SL/DL-HT Features:

- Lead free capable
- Large 13" x 13" heating area
- 3/4" thick aluminum heat plates for precise, even heating
- Programmable digital temperature controller precisely and automatically regulates temperatures
- Model GF-DL-HT is the same as GF-SL-HT above but with two independent temperature controls and dual 13" x 6.4" plates.

Model GF-DL-HT SPECIFICATIONS	
Electrical Power**	110 VAC, 50/60, 20A
Power	900 W each plate
Temperature Range High Temp: GF-DL-HT	100° to 600°F (37° to 315°C)
Heating Area (x2)	13" x 6.4" (330x163mm)
Dimensions	22.63" x 15.25" x 4.50" (575 x 387 x 114 mm)
Approximate Weight	35 lbs (16Kg)

Model GF-SL-HT SPECIFICATIONS	
Electrical Power**	110 VAC, 50/60,
Power	1800 W
Temperature Range High Temp: GF-SL-HT	100° to 600°F (37° to 315°C)
Heating Area	13" x 13" (330x330mm)
Dimensions	22.63" x 15.25" x 4.50" (575 x 387 x 114 mm)
Approximate Weight	35 lbs (16Kg)

*For use with lead free solder alloys.
**Other electrical configurations available.